

Ref: **PFG-52/P**
Convobis Line
Gas convection oven 5xEN(GN),
automatic humidifier



Your professional partner

Brand : DIAMOND



2 speeds



·mm (BxDxH) :947x791xh745

·kcal/h :9050

·kW :0,6

·Volt : 230/1N 50Hz

·kg : 120

·M³ : 0,79

- Internal dimensions 645x460xh400
- Standard equipment: 1 grid EN 600x400
- 1 "autoreverse" turbine
- Welded room in stainless steel (AISI 304).
- (Predisposition for fat filter), rounded edges and angles, pressed bottom with draining (possibility of closing).
- Removable carrying-plate structure (67 mm).
- Chimney for evacuation of the condensate, (manually) adjustable.
- Interior lighting.
- Built-in condensate bowl (on the door), connected directly to the discharge.
- Double glazing door (option: door with hinges on the right), interior window on hinges, ergonomic and athermal handle, automatic closing, (removable) gasket joint.
- Micro-switch to stop the fan when the door opens.
- Gas heating: stainless steel burner with stabilized flame, safety with thermocouples, automatic lighting by pilot light.
- Regulation from 50 to 270°C, timer from 1 to 120 min. (or) continuous, electronic thermometer.
- Safety thermostat.
- Manufactured in stainless steel.
- Adjustable stainless steel feet.
- Manufactured in line with the standards (CE) in force.

ADVANTAGE:

Everybody knows that "He who can do more, can do less"... Why should we content ourselves with the main thing, the mediocrity if we can have much more!!!... ConvoBis, a new generation of ovens, (Polyvalents EN 600x400 & GN 1/1), homogeneous and fast cooking, delicate cooking, succeed also the finest ones.

- "Autoreverse" turbines, 2 ventilation speeds 1500/2800 turns /minutes.
- Automatic humidifier "nebulization", gradual regulation of the humidification level of the chamber.
- Big range of accessories, supports, levitation chamber...