

Ref: IE70/R2

Gastro Line PLUS

Ventilated freezer 700 liters, 1 door GN

2/1, on wheels



Your professional partner

Brand : DIAMOND



·mm (BxDxH) :720x850x2070

·T° : -15° -25°

·kW :0,63

·Volt : 230/1N 50Hz

·kg : 156

·M³ : 1,49

- Energy class: D (very important, "HEAVY DUTY" cabinets certified in climate class 5 "40 ° C Temperature - 40% Humidity")

- Included: 3 grids GN 2/1 (530x650 mm).

- Refrigerant R290.

- Inner door with warming resistance.

- Depression valve, standard delivered.

- Delivered with 4 wheels, 2 with brakes.

- Manufactured in stainless steel, interior AISI 304, exterior AISI 441 (back in treated steel, gray), monocoque frame.

- Stainless steel rack and slides (anti-tilting), allowing to place the grids as ones pleases.

- Stamped interior bottom, rounded angles and corners (without roughness).

- Bottom fitted with a draining tap (high maintenance).

- Doors with ergonomic handle (no salient) and reversible (predisposition for key lock), "snap-fit" closure by magnetic joint (easy replacement without tools), hinge with stop at 100° and closure of the doors with automatic return.

- Micro-switch device, allowing the ventilator's stop, while opening the door.

- Upper panel for the accessibility of the compressor, on hinges, easy inspection.

- Refrigerated group at "tampon", tropicalized, and ventilated condenser.

- Ventilated evaporator(s) Evaporator treated against salts and food acids "coating", completely hidden (non visible).

- Refrigerant expansion by capillary.

- Electronic regulator (under waterproof closed box), control front screen with blue LED.

- Intern lighting, with switch.

- Automatic defrosting of the evaporator, number of defrosting programmed by factory (modifiable at will).

- Condenser's automatic evaporation.

- Polyurethane insulation without CFC (75 mm).

- The equipment is manufactured following the (CE) standards in force.

PLUS - HIGH EFFICIENCY :

- Componentes in high efficiency and low energy consumption.

- Polyurethane insulation without CFC (80 mm = super insulated), less thermal dispersion, with energy saving in addition.

- Refrigerated group at "tampon", (in insulated box), tropicalized (climatic class 5 "ambient T° +40°C - Humidity40%").

- Exceptional services thanks to the 2 evaporators (1400 liters), allowing an uniform temperature (airflow 100% optimized),, guaranteeing the good preserving of the products.

- Double runner slides (allowing grids and trays GN at the same time!!).

- Easy work thanks to the hinges with stop at 100° and closure of the doors with automatic recall.

- Electronic regulator (under closed waterproof box) with HACCP functions.

- Standard delivered with 4 wheels, easy displacement for cleaning and maintenance.